

GENERATING SET GA 1400 SX

- Kawasaki, gasoline engine
- Engine shut down (oil)
- Single-phase synchronous alternator
- Battery charger 12V - 8.5A
- Silenced
- Portable
- Meets EEC directives



Standard equipment 													
	Gasoline engine	Air cooling	Manual recoil	Engine shut down (oil)	Tank fuel with fuel gauge								
	Synchronous alternator	Thermal shut off	Socket 230V Schuko	Battery charger									

Options on request ● Plug 230V 16A 2PT (M) SCHUKO

Technical Data

GA 1400 SX

A.C. GENERATION 50/60 Hz, synchronous, single-phase, self-excited, self-regulated, brushless

Rated (max) single-phase power	1050 (1200 max) VA / 230V / 4.5 A(50 Hz) 1200 (1400 max) VA / 230V / 5.2 A(60 Hz)
Battery charger d.c.	12V - 8.5A
Duty cycle	100%
Power factor (Cos φ)	1

ENGINE Gasoline, 4-stroke, air cooled

Type	Kawasaki FA 130 D
Output*	2.3 kW (3.1 HP)
Speed	3000 (50 Hz) - 3600 (60 Hz) rpm
Displacement	129 cm ³
Cylinders	1
Fuel consumption	231 g/kWh
Oil capacity	0.5 l

* Maximum output according to ISO 3046/1

GENERAL SPECIFICATIONS

Tank capacity	4.5 l
Running time (Load 75%)	9 h
Protection	IP 23
Dimensions Lxwxh (mm)	460x304x400
Weight	27 kg
Noise level	90 LWA (65 dB(A) - 7 m) (50 Hz) - 92 LWA (67 dB(A) - 7 m) (60 Hz)

Values shown are nominal values. For further information please contact the sales department.